

GRUPPO INCASSO MURANO

Version

Built-in 50 cm - Black - 800 m³/h

Collection

Design

EAN code

8034122359458



*The photograph is purely for information
It may not correspond to the selected version.*

FEATURES

Touch control + 24 h function
Metallic grease filter, removable and washable
Charcoal filter included
Remote control included
Perimeter suction with tempered glass panel
Dynamic LED Light (2700K - 5600K)

OPTIONAL ACCESSORIES

KACL.934

Carbon.Zeo filters

KACL.950

Filter unit for built-in hoods

101079910

Metallic filter "Base" - 204x207 mm

103050091

Round charcoal filter Ø170 mm - Type 6

TECHNICAL FEATURES

Installation type

Built-in

Dimensions

50 cm

Finishing

Black tempered glass
Painted black steel

Motor

800 m³/h

Type of control

Touch control

Speed settings

4

Lighting

Led 2x2,4 W - 2700 K / 5600 K

Filter

Metallic filter "Base" - 204x207 mm

Charcoal filter

Round charcoal filter Ø170 mm - Type 6 (included)

Minimum distance

Gas hob: 62 cm

Electric hob: 52 cm

PACKAGING:WEIGHTS AND VOLUMES

Gross weight

10 kg

Net weight

8.1 kg

Volumes

0.09 m³

Packaging size

Length

610 mm

Height

380 mm

Depth

375 mm

CONSUMPTION AND CONNECTION FEATURES

Maximum consumption

280 W

Voltage

220-240V

Frequency

50-60Hz

Plug type

Shuko

MOTOR TECHNICAL SHEET

Maximum capacity

670 m³/h

I.E.C. 61591

Maximum noise level

67 dB(A)re1pW

I.E.C.60704-2-13

Maximum pressure (Pa)

500 Pa

Max. motor power

215 W

ENERGY CLASS

B

GRUPPO INCASSO MURANO

Version

Built-in 50 cm - Black - 800
m³/h

Collection

Design


EAN code

8034122359458

MOTOR TECHNICAL SHEET

Motor speed	1	2	3	4
Noise level dB(A) _{re1pW-I.E.C.60704-2-13}	49	55	61	67
Capacity (m ³ /h) I.E.C.61591	270	360	470	670
Maximum pressure (Pa)	390	420	460	500
Motor Power (W)	134	156	180	215
Air outlet	150	150	150	150

CAPACITY / PRESSURE



GRUPPO INCASSO MURANO

Version

Built-in 50 cm - Black - 800 m3/h


Collection

Design

EAN code

8034122359458

ENERGY LABEL



PF		
S	Falmec Spa	
M	Built-in 50 cm - Black - 800 m3/h	
AEC	65,9	kWh/a
EEC	B	
FDE	25,5	
FDEC	B	
LE	21,6	
LEC	B	
GFE	53,0	
GFEC	F	
Qmin	270,0	m ³ /h
Qmax	470,0	m ³ /h
Qboost	670,0	m ³ /h
SPEmin	49	dBa
SPEmax	61	dBa
SPEboost	67	dBa
PO	-	W
PS	0,48	W
PI		
F	1,1	
EEL	64,9	
Qbep	333,0	m ³ /h
Pbep	407	Pa
Qboost	670,0	m ³ /h
Wbep	147,7	W
WL	9,00	W
Emiddle	190	lux
Lwa-SPEmax	61	dBa

PF_Product fiche according to 65/2014 S_Supplier name / M_Model identification / AEC_Annual Energy Consumption (AEC hood) / EEC_Energy Efficiency class / FDE_Fluid Dynamic Efficiency (FDE hood) / FDEC_Fluid Dynamic Efficiency class / LE_Lighting Efficiency (LE hood) / LEC_Lighting Efficiency class / GFE_Grease Filtering Efficiency / GFEC_Grease Filtering Efficiency class / Qmin_Air flow (in m³/h) at min speed in normal use / Qmax_Air flow (in m³/h) at max speed in normal use / Qboost_Air flow (in m³/h) at intensive or boost setting (max air-flow) / SPEmin_Airborne acoustical A-weighted sound power emissions at min speed in normal use / SPEmax_Airborne acoustical A-weighted sound power emissions at max speed in normal use / SPEboost_Airborne acoustical A-weighted sound power emissions (in dB) at intensive or boost setting / PO_Power consumption in off mode (Po) / Ps_Power consumption in stand by mode (Ps). **PI_Additional information according to 66/2014** F_Time increase factor / EEL_Energy Efficiency Index / Qbep_Measured air flow rate at best efficiency point / Pbep_Measured air pressure at best efficiency point / Qboost_Maximum air flow / Wbep_Measured electric power input at best efficiency point / WL_Nominal power of the lighting system / Emiddle_Average illumination of the lighting system on the cooking surface / Lwa-SPEmax_Sound pressure level at the highest speed.